

CIRRUS® Classic Motifs™

Bistro™, Cotillion™ & Embassy™

Tegular

fine texture



Cirrus Classic Motifs Bistro with Suprafine®
9/16" Exposed Tee Grid



Cirrus Classic Motifs Cotillion with Suprafine®
9/16" Exposed Tee Grid



Cirrus Classic Motifs Embassy with Suprafine®
9/16" Exposed Tee Grid

Key Selection Attributes

- Three sculpted designs on fine Cirrus refined texture
- Excellent sound absorption
- 30-Year Limited System Warranty against mold/mildew and bacterial growth

Typical Applications

- Lobbies/reception areas
- Department stores/retail
- Specialty shops
- Dining areas
- Offices
- Healthcare – assists in addressing HIPAA requirements
- Conference rooms

Detail



CIRRUS Classic Motifs
Beveled Tegular
Plain Panel



CIRRUS Classic Motifs
Cotillion



CIRRUS Classic Motifs
Bistro



CIRRUS Classic Motifs
Embassy

Color



White (WH)

CIRRUS® Classic Motifs™

Bistro™, Cotillion™ & Embassy™

Tegular

fine texture

Recycled Content: 65-83%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views	LEED for Schools	
✓	✓	✓	✓	✓	✓	Acoustics	Low Emitting or CHPS
			Location Dependent				✓

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified Acoustics NRC CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program	
											UL Classified
CIRRUS Classic Motifs Bistro*											
9/16" Beveled Tegular	518	2' x 2' x 3/4"	□ 0.65 35	Class A	0.86	S	BioBlock+	No Added	S	Yes	
CIRRUS Classic Motifs Cotillion*											
9/16" Beveled Tegular	524	2' x 2' x 3/4"	□ 0.65 35	Class A	0.86	S	•	No Added	S	•	
CIRRUS Classic Motifs Embassy*											
9/16" Beveled Tegular	526	2' x 2' x 3/4"	□ 0.65 35	Class A	0.86	S	•	No Added	S	•	
CIRRUS Classic Motifs Plain Panel – Specify panel 6498 when plain panels are required.											
9/16" Beveled Tegular	6498†	2' x 2' x 3/4"	□ 0.65 35	Class A	0.86	S	•	No Added	S	•	
	6498M	600 x 600 x 19mm									

S = Standard

† Available with Hardware Friendly Options (U.S. Patent 5,231,810)

* Ceiling design copyrighted by AWI Licensing Company

Suspension Systems

9/16" Standard: Suprafine®

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

6498 – Type III, Form 1, Pattern E I
518, 524, 526 – Type III, Form 1, Pattern E J
Fire Class A

No-Added Formaldehyde

No-added formaldehyde – free of formaldehyde-based resins. Outperform CHPS Section 01350 requirements. (Independent test reports available upon request.)

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 1.9 (BTU units)
R Factor – 0.33 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

30-Year Performance Guarantee & Warranty Information

See warranty details at armstrong.com/warranty

Application Considerations

Specify matching plain panel 6498 when required.

Not recommended for rooms containing MRI equipment.

Weight; Square Feet/Carton

1.17 lbs/SF; 48 SF/ctn

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: cirrus)
CS-3055-109

© AWI Licensing Company, 2009 • Printed in the United States of America

